




US 20140283408A1

(19) **United States**(12) **Patent Application Publication**
Chun et al.(10) **Pub. No.: US 2014/0283408 A1**(43) **Pub. Date: Sep. 25, 2014**(54) **VACUUM ASSISTED DEHYDRATION
SYSTEM**(71) Applicant: **Hankookin, Inc.**, Raleigh, NC (US)(72) Inventors: **James Jiwen Chun**, Raleigh, NC (US);
Andrew Youngho Chun, Raleigh, NC
(US); **Angela Soyoung Chun**, Raleigh,
NC (US); **Jennifer Miseong Chun**,
Raleigh, NC (US)(73) Assignee: **Hankookin, Inc.**, Raleigh, NC (US)(21) Appl. No.: **14/217,370**(22) Filed: **Mar. 17, 2014****Related U.S. Application Data**(60) Provisional application No. 61/803,196, filed on Mar.
19, 2013.**Publication Classification**(51) **Int. Cl.**
A61L 2/02 (2006.01)(52) **U.S. Cl.**CPC **A61L 2/02** (2013.01)USPC **34/412; 34/92**(57) **ABSTRACT**

A vacuum assisted dehydration system including a vacuum chamber, a gas compressor, a heating coil, and a vacuum pump is provided. A sealing member removably attached to an opening of the vacuum chamber is opened to introduce one or more instruments into the vacuum chamber. The gas compressor, in fluid communication with the vacuum chamber, recirculates a pressurized gas into the vacuum chamber. The heating coil within the vacuum chamber heats the recirculating gas, which contacts the instruments positioned therein and transfers heat energy into interstitial cavities and to surfaces of the instruments or onto other moist components, for example, hands to vaporize moisture present therein. The vacuum pump, in fluid communication with the vacuum chamber, creates a negative gas pressure in the vacuum chamber to exhaust the vaporized moisture entrained in the heated recirculating gas from the vacuum chamber to dehydrate the instruments or the moist components.






FIG. 1




FIG. 2




FIG. 3A

FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5





FIG. 6






FIG. 8




FIG. 9B




FIG. 10





FIG. 11A

**FIG. 11B**

VACUUM ASSISTED DEHYDRATION SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to and the benefit of provisional patent application No. 61/803,196 titled "Vacuum Assisted Dehydration System", filed in the United States Patent and Trademark Office on Mar. 19, 2013. The specification of the above referenced patent application is incorporated herein by reference in its entirety.

BACKGROUND

[0002] Maintenance of dental instruments, for example, dental turbines and dental handpieces, is a difficult task. Rotating components incorporated in dental instruments are delicate and complex devices. In a clinical assessment, cleaning and lubrication of high speed handpieces have been found to be critical in determining their performance and durability. A manufacturer's instructions for cleaning, lubrication, and sterilization should be followed correctly to ensure the efficiency of the process and the longevity of the handpieces.

[0003] Sterilization of medical and dental instruments is required in medical offices and dental offices. Moist heat sterilization under high pressure and a high temperature, which are well known in the art, are used for sterilizing medical and dental instruments. However, moist heat sterilization at high pressure and high temperature can cause permanent damage to medical and dental instruments, for example, high speed handpieces. Dental high speed handpieces are known to be very difficult and costly to moist heat sterilize and maintain. One possible cause of damage to a high speed handpiece is chemical corrosion of a metal component therewithin due to the presence of water or moisture on the surfaces or interstitial cavities of the high speed handpiece. Moisture that resides in interstitial cavities of high speed handpieces is generally not removed by conventional pre-sterilization cleaning methods such as manual scrubbing, air driven oiling using specialized appliances, for example, Assistina™ of the W & H Group, Austria, etc. Moisture tends to condense within the interstitial cavities even after substantial pre-sterilization cleaning due to the complex geometries and interstitial cavities in the high speed handpieces. This moisture may mix with lubrication oil that may be present in the high speed handpiece and cause damage to the high speed handpiece during sterilization at elevated temperatures and during normal usage of the high speed handpiece. If water and moisture can be completely removed during the pre-sterilization cleaning process, damage to the high speed handpiece during sterilization and normal usage can be substantially reduced.

[0004] Hence, there is a long felt but unresolved need for a vacuum assisted dehydration system that dehydrates one or more instruments, for example, medical instruments, dental instruments, etc., using a negative gas pressure to remove moisture from the instruments, for example, before a lubrication process to maximize lubrication of instrument turbines to extend the useful life of the instruments.

SUMMARY OF THE INVENTION

[0005] This summary is provided to introduce a selection of concepts in a simplified form that are further disclosed in the detailed description of the invention. This summary is not

intended to identify key or essential inventive concepts of the claimed subject matter, nor is it intended for determining the scope of the claimed subject matter.

[0006] The vacuum assisted dehydration system disclosed herein addresses the above mentioned need for dehydrating one or more instruments using a negative gas pressure. As used herein, the term "dehydration" refers to a process of removing moisture from an interstitial cavity or a surface of an object such as a dental instrument. Also, as used herein, the term "instruments" refers, for example, to components, devices, tools, appliances, apparatuses, equipment, etc., used in fields such as medicine, dentistry, etc. The instruments comprise, for example, dental instruments such as a high speed handpiece, a slow speed motor attachment, a cheek retractor, a tongue retractor, etc., medical instruments such as needles, scalpel blades, etc. Also, as used herein, "negative gas pressure" refers to a state of vacuum created in an inner enclosed space within a closed chamber. The vacuum assisted dehydration system disclosed herein can be used to remove moisture from the instruments, for example, before a lubrication process to maximize lubrication of instrument turbines to extend the useful life of the instruments.

[0007] The vacuum assisted dehydration system disclosed herein comprises a generally cylindrical vacuum chamber, a sealing member, and a vacuum pump. The vacuum chamber defines an inner enclosed space for accommodating one or more instruments, for example, dental instruments. The sealing member is removably attached to a first opening defined at a first opposing end of the vacuum chamber. The sealing member is opened to allow one or more instruments to be introduced into the inner enclosed space of the vacuum chamber. In an embodiment, the sealing member is a metallic cap concentrically aligned with a washer. The metallic cap is fastened through threads configured at the first opening defined at the first opposing end of the vacuum chamber. In another embodiment, the sealing member is a push fit seal comprising a metallic cap and a washer. The sealing member push fits to the first opening defined at the first opposing end of the vacuum chamber to facilitate an air tight seal of the vacuum chamber. In an embodiment, the sealing member is made of a metallic material having a low coefficient of thermal expansion to avoid expansion of the sealing member due to heat produced by the heating coil.

[0008] The vacuum pump is operably connected to a second opening defined at a second opposing end of the vacuum chamber. The vacuum pump is in fluid communication with the vacuum chamber via the second opening. The vacuum pump is, for example, a multistage centrifugal vacuum pump or a multistage reciprocating vacuum pump. In an embodiment, the vacuum pump is operably connected to the second opening of the vacuum chamber through a flexible tube, for example, a hose, a pipe, etc. The vacuum pump creates a negative gas pressure in the inner enclosed space of the vacuum chamber to dehydrate the accommodated instruments after the vacuum chamber is closed by the sealing member. In an embodiment, the vacuum assisted dehydration system disclosed herein further comprises a heating coil positioned on an inner surface wall of the vacuum chamber. The heating coil heats a recirculating gas in the inner enclosed space of the vacuum chamber, which facilitates the removal of moisture from the instruments placed in the vacuum chamber and accelerates the dehydration of the instruments.

[0009] In an embodiment, the vacuum assisted dehydration system disclosed herein further comprises a gas compressor

and a gas inlet port, in addition to the generally cylindrical vacuum chamber, the sealing member, the heating coil, and the vacuum pump disclosed above. The vacuum chamber comprises a surface wall defining an inner enclosed space for accommodating one or more instruments. The surface wall of the vacuum chamber is made of, for example, aluminum, stainless steel, etc. The surface wall of the vacuum chamber reflects heat. In an embodiment, the vacuum assisted dehydration system disclosed herein further comprises a condenser in upstream communication with the vacuum pump via a vacuum pump outlet pipe, and in downstream communication with the gas compressor via a condenser outlet pipe. The gas compressor is positioned proximal to and in fluid communication with the vacuum chamber via an inlet tube. The gas compressor recirculates a gas pressurized to a preset pressure into the inner enclosed space of the vacuum chamber via the inlet tube. In an embodiment, the gas is an inert gas, for example, argon. The gas compressor pressurizes the inert gas to a preset pressure in a range of between about 15 psig to about 40 psig. For example, the gas pressure is preset at a pressure of about 16 psig. The gas compressor pumps the recirculating gas via the inlet tube to the inner enclosed space within the vacuum chamber.

[0010] The gas inlet port is defined on the surface wall of the vacuum chamber. The gas inlet port is in fluid communication with the gas compressor via the inlet tube. The recirculating gas from the gas compressor is fed into the inner enclosed space of the vacuum chamber through the gas inlet port via the inlet tube. The heating coil is operably positioned on the inner surface wall of the vacuum chamber. The heating coil is, for example, an electric heating coil. The heating coil heats the recirculating gas in the inner enclosed space of the vacuum chamber to a preset temperature of, for example, between about 30° Celsius (C) to about 75° C. The heated recirculating gas contacts the instruments positioned in the inner enclosed space of the vacuum chamber and transfers heat energy into interstitial cavities and to the surfaces of the instruments to vaporize moisture present in the interstitial cavities and on the surfaces of the instruments. The interstitial cavities comprise, for example, needle grooves, narrow and deep fluid transfer lines, etc., in the instruments. The surfaces of the instruments, for example, cover a total surface area of the instruments including surfaces defined by the interstitial cavities. In an embodiment, the vacuum assisted dehydration system further comprises safety switches operably connected to the heating coil to regulate the temperature to a predetermined level in the inner enclosed space of the vacuum chamber.

[0011] The vacuum pump creates a negative gas pressure in the inner enclosed space of the vacuum chamber to dehydrate the accommodated instruments after the vacuum chamber is closed by the sealing member, and exhausts the vaporized moisture entrained in the heated recirculating gas from the inner enclosed space of the vacuum chamber to the condenser. In an embodiment, the vacuum assisted dehydration system further comprises one or more pressure control valves operably connected to the vacuum pump for controlling an amount of the negative gas pressure created within the inner enclosed space of the vacuum chamber to protect the accommodated instruments within the vacuum chamber.

[0012] The condenser, operably connected to and in fluid communication with the vacuum pump of the vacuum assisted dehydration system, receives the vaporized moisture entrained in the heated recirculating gas from the vacuum

pump. The vaporized moisture entrained in the recirculating gas is exhausted from the vacuum chamber by the vacuum pump to the condenser. The condenser condenses and reduces moisture from the vaporized moisture entrained in the heated recirculating gas, for example, by contacting the vaporized moisture entrained in the heated recirculating gas with a heat exchange surface such as a coil through which a refrigerant is recirculating at a temperature of, for example, about 10° C. to about -2° C. When the vaporized moisture entrained in the heated recirculating gas contacts the refrigerant coil, the moisture condenses out and is drained out from the condenser. The moisture reduced, low humidity recirculating gas is exhausted from the condenser to the gas compressor.

[0013] In an embodiment, instead of the vacuum pump, the vacuum assisted dehydration system disclosed herein further comprises a suction line, for example, a medical suction line or a dental suction line, operably connected to the second opening of the vacuum chamber. The suction line produces a vacuum having a vacuum pressure of, for example, about 29 inches of mercury within the inner enclosed space of the vacuum chamber.

[0014] In an embodiment, a vacuum assisted dehydration system for dehydrating one or more components containing moisture on the surface of the components, herein referred to as “moist components”, for example, a user’s moist hands, moist gloves, etc., in a dental or a medical environment is provided. In this embodiment, the vacuum assisted dehydration system disclosed herein comprises the generally cylindrical vacuum chamber, the condenser, the gas compressor, the gas inlet port, the heating coil, and the vacuum pump, without the sealing member. In this embodiment, the first opening defined at the first opposing end of the vacuum chamber is configured to receive the moist components into the inner enclosed space of the vacuum chamber. The recirculating gas received from the gas compressor is heated by the heating coil and the heated recirculating gas contacts the moist components positioned in the inner enclosed space of the vacuum chamber and transfers heat energy to the moist components to vaporize moisture off the moist components. The vacuum pump creates a negative gas pressure in the inner enclosed space of the vacuum chamber to dehydrate the moist components and exhausts the vaporized moisture entrained in the heated recirculating gas from the inner enclosed space of the vacuum chamber to the condenser. The vacuum assisted dehydration system disclosed herein provides a transient dehydration region in the inner enclosed space of the vacuum chamber for dehydrating the moist components by recirculating the gas from the gas compressor into the inner enclosed space of the vacuum chamber, heating the recirculating gas using the heating coil, allowing the heated recirculating gas to contact the moist components, and exhausting the vaporized moisture entrained in the heated recirculating gas from the moist components via the vacuum pump.

[0015] In an embodiment, the vacuum assisted dehydration system disclosed herein further comprises a rotary disk assembly positioned on an inner surface wall of the vacuum chamber. The rotary disk assembly comprises a disk member and an electric motor. The disk member is axially aligned and fixedly connected to the electric motor. The disk member fixedly accommodates one or more instruments. The electric motor rotates the disk member at a sufficient speed to generate a centrifugal force sufficient to force the moisture present in the interstitial cavities and on the surfaces of the accommodated instruments to open ends or open surfaces of the

accommodated instruments for removal by the recirculating gas fed by the gas compressor into the inner enclosed space of the vacuum chamber, by the recirculating gas heated by the heating coil, and by the negative gas pressure created in the vacuum chamber by the vacuum pump.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The foregoing summary, as well as the following detailed description of the invention, is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, exemplary constructions of the invention are shown in the drawings. However, the invention is not limited to the specific methods and structures disclosed herein. The description of a structure or a method step referenced by a numeral in a drawing carries over to the description of that structure or method step shown by that same numeral in any subsequent drawing herein.

[0017] FIG. 1 exemplarily illustrates a top perspective view of a vacuum assisted dehydration system comprising a generally cylindrical vacuum chamber, a sealing member, and a vacuum pump.

[0018] FIG. 2 exemplarily illustrates a top perspective view of an embodiment of the vacuum assisted dehydration system comprising the generally cylindrical vacuum chamber, the sealing member, the vacuum pump, a condenser, and a gas compressor.

[0019] FIG. 3A exemplarily illustrates a cutaway view of the embodiment of the vacuum assisted dehydration system shown in FIG. 2, showing one or more instruments accommodated in an inner enclosed space of the vacuum chamber.

[0020] FIG. 3B exemplarily illustrates an enlarged view of a portion marked A in FIG. 3A of the embodiment of the vacuum assisted dehydration system, showing interstitial cavities and surfaces of an instrument.

[0021] FIG. 4A exemplarily illustrates a top perspective view of an embodiment of the vacuum assisted dehydration system, showing a threadable connection of the sealing member to an opening of the vacuum chamber.

[0022] FIG. 4B exemplarily illustrates a top perspective view of another embodiment of the vacuum assisted dehydration system, showing a push fit connection of the sealing member to an opening of the vacuum chamber.

[0023] FIG. 5 exemplarily illustrates a rear perspective view of a heating coil of an embodiment of the vacuum assisted dehydration system, showing safety switches operably connected to the heating coil.

[0024] FIG. 6 exemplarily illustrates a top perspective view of the vacuum pump of an embodiment of the vacuum assisted dehydration system, showing a pressure control valve connected to the vacuum pump.

[0025] FIG. 7 exemplarily illustrates a cutaway view of an embodiment of the vacuum assisted dehydration system, showing a suction line connected to an opening of the vacuum chamber.

[0026] FIG. 8 exemplarily illustrates a top perspective view of an embodiment of the vacuum assisted dehydration system, showing components the surface of which are moist, introduced into an inner enclosed space of the vacuum chamber via an opening.

[0027] FIG. 9A exemplarily illustrates a cutaway view of an embodiment of the vacuum assisted dehydration system, showing a rotary disk assembly positioned in the vacuum chamber.

[0028] FIG. 9B exemplarily illustrates an enlarged view of a portion marked B in FIG. 9A of the embodiment of the vacuum assisted dehydration system, showing interstitial cavities and surfaces of an instrument.

[0029] FIG. 10 exemplarily illustrates a block diagram showing a process for dehydrating instruments within the vacuum assisted dehydration system.

[0030] FIGS. 11A-11B exemplarily illustrate a method for dehydrating one or more instruments.

DETAILED DESCRIPTION OF THE INVENTION

[0031] FIG. 1 exemplarily illustrates a top perspective view of a vacuum assisted dehydration system **100** comprising a generally cylindrical vacuum chamber **101**, a sealing member **103**, and a vacuum pump **105**. The vacuum assisted dehydration system **100** dehydrates one or more instruments **108** by creating a negative gas pressure within the vacuum chamber **101**. As used herein, the term “dehydration” refers to a process of removing moisture or water, herein “moisture”, from an interstitial cavity or a surface of an object such as a dental instrument. Also, as used herein, the term “instruments” refers, for example, to components, devices, tools, appliances, apparatuses, equipment, etc., used in fields such as medicine, dentistry, etc. The instruments **108** comprise, for example, dental instruments such as a high speed hand piece, a slow speed motor attachment, a cheek retractor, a tongue retractor, etc., medical instruments such as needles, scalpel blades, etc. Also, as used herein, “negative gas pressure” refers to a state of vacuum created in an inner enclosed space **102** within the vacuum chamber **101**. The vacuum chamber **101** defines an inner enclosed space **102** therewithin for accommodating one or more instruments **108**. The vacuum chamber **101** is configured, for example, as an air tight metal cylinder. The vacuum chamber **101** is manufactured in predetermined sizes depending on the sizes of the instruments **108** to be accommodated therewithin. The vacuum chamber **101** is made of metallic materials, for example, aluminum, stainless steel, etc. The sealing member **103** is removably attached to a first opening **104** defined at a first opposing end **101a** of the vacuum chamber **101**. The sealing member **103** is configured to be positioned over the first opening **104** to open and close the vacuum chamber **101** to allow instruments **108** to be introduced into and removed out of the inner enclosed space **102** of the vacuum chamber **101**.

[0032] The vacuum pump **105** is operably connected to a second opening **106** defined at a second opposing end **101b** of the vacuum chamber **101**. The vacuum pump **105** is in fluid communication with the vacuum chamber **101** via the second opening **106**. The vacuum pump **105** creates a preset negative gas pressure, for example, a negative pressure of between about 2 inches of mercury to about 29 inches of mercury in the inner enclosed space **102** of the vacuum chamber **101** to dehydrate the accommodated instruments **108** after the vacuum chamber **101** is closed by the sealing member **103** and the vacuum pump **105** is turned on.

[0033] In an embodiment, the vacuum assisted dehydration system **100** disclosed herein further comprises a heating coil **107** for heating a recirculating gas in the inner enclosed space **102** of the vacuum chamber **101**, which facilitates removal of moisture from the instruments **108** placed in the vacuum chamber **101** and accelerates the dehydration of the accommodated instruments **108**.

[0034] FIG. 2 exemplarily illustrates a top perspective view of an embodiment of the vacuum assisted dehydration system

100. In this embodiment, in addition to the generally cylindrical vacuum chamber **101**, the sealing member **103**, and the vacuum pump **105** disclosed in the detailed description of FIG. 1, the vacuum assisted dehydration system **100** further comprises a gas compressor **109** and a condenser **110**. The gas compressor **109** is, for example, a small sized hermetically sealed gas compressor, used to recirculate gas pressurized to a preset pressure between about 16 psig to about 20 psig into the vacuum chamber **101**. As an example, in many dental offices, the pressurized gas or compressed air is also available from dental compressors that produce air pressure up to, for example, about 29 inches of mercury. In another example, the pressurized gas is also available from dental compressors that produce pressurized gas, for example, at about 15 psig to about 40 psig.

[0035] The vacuum pump **105**, operably connected at the second opposing end **101b** of the vacuum chamber **101** and in fluid communication with the vacuum chamber **101**, creates a preset negative gas pressure, for example, a negative pressure of between about 2 inches of mercury to about 29 inches of mercury in the vacuum chamber **101** to dehydrate the instruments **108** accommodated in the vacuum chamber **101** as exemplarily illustrated in FIG. 3A. The condenser **110** is operably connected to and in fluid communication with the vacuum pump **105** to receive vaporized moisture entrained in the recirculating gas from the vacuum pump **105**. The condenser **110** condenses out and reduces moisture from the vaporized moisture entrained in the recirculating gas as disclosed in the detailed description of FIGS. 3A-3B.

[0036] As used herein, “gas” refers to air or an inert gas that is recirculated in the loop comprising the vacuum chamber **101**, the vacuum pump **105**, the condenser **110**, and the gas compressor **109**. The recirculating gas is supplied at a low to moderate pressure, preset at a pressure of between about 15 psig to about 40 psig from the gas compressor **109** to the inner enclosed space **102** within the vacuum chamber **101** exemplarily illustrated in FIG. 3A. The inner enclosed space **102** within the vacuum chamber **101** is maintained at a negative pressure, for example, preset at a negative pressure of between about 2 inches of mercury and about 29 inches of mercury to allow the moisture in the interstitial cavities **117** and on surfaces **118** of the instruments **108** exemplarily illustrated in FIG. 3B, to volatilize off the instruments **108** and be entrained in the recirculating gas circulating in the loop. In an embodiment, the recirculating gas in the inner enclosed space **102** within the vacuum chamber **101** is heated by a heating coil **107** positioned in the inner enclosed space **102** as exemplarily illustrated in FIG. 3A, to a preset temperature of, for example, between about 30° Celsius (C) to about 75° C. to facilitate the removal of the moisture from the instruments **108** by increasing the temperature of the instruments **108** and the moisture contained in the interstitial cavities **117** or surfaces **118** of the instruments **108**. The vaporized moisture entrained in the recirculating gas from the vacuum chamber **101** is exhausted by the vacuum pump **105** to the condenser **110**, where the moisture in the recirculating gas is condensed out by dropping the temperature of the vaporized moisture entrained in the recirculating gas to a preset temperature, for example, between about -2° C. and about 10° C. in the condenser **110**.

[0037] FIG. 3A exemplarily illustrates a cutaway view of the embodiment of the vacuum assisted dehydration system **100** shown in FIG. 2, showing one or more instruments **108** accommodated in the inner enclosed space **102** of the vacuum

chamber **101**. As exemplarily illustrated in FIG. 3A, the vacuum assisted dehydration system **100** disclosed herein comprises the vacuum pump **105**, the condenser **110**, the gas compressor **109**, the generally cylindrical vacuum chamber **101**, the heating coil **107**, and the sealing member **103**. The vacuum chamber **101** comprises a surface wall **111** defining the inner enclosed space **102**. The surface wall **111** of the vacuum chamber **101** is, for example, made of aluminum. The inner enclosed space **102** accommodates one or more instruments **108**. The surface wall **111** of the vacuum chamber **101** reflects heat. The sealing member **103** is removably attached to a first opening **104** defined at a first opposing end **101a** of the vacuum chamber **101**. The sealing member **103** is used to open the vacuum chamber **101** to allow instruments **108** to be introduced into the inner enclosed space **102** of the vacuum chamber **101** and is thereafter closed prior to the vacuum pump **105** being turned on.

[0038] In this embodiment, the condenser **110** is in upstream communication with the vacuum pump **105** via a vacuum pump outlet pipe **119**, and in downstream communication with the gas compressor **109** via a condenser outlet pipe **120**. The condenser **110** condenses and reduces the moisture in a recirculating gas, for example, by lowering the temperature of the recirculating gas by contacting the recirculating gas with a heat exchange surface such as a coil **110a** through which a refrigerant is circulating at a temperature preset, for example, at a temperature between about 10° C. to about -2° C. as exemplarily illustrated in FIG. 10. When the recirculating gas with the entrained moisture **116** contacts the refrigerant coil **110a**, the moisture condenses out and is drained from the condenser **110**.

[0039] The recirculating gas with the low humidity, reduced moisture content from the condenser **110** is fed to the gas compressor **109**. The gas compressor **109** is positioned proximal to and in fluid communication with the vacuum chamber **101** via an inlet tube **112**. The gas compressor **109** feeds the recirculating gas **113** into the inner enclosed space **102** of the vacuum chamber **101** via the inlet tube **112**. In an embodiment, the recirculating gas **113** is an inert gas, for example, argon. A gas inlet port **114** is defined on the surface wall **111** of the vacuum chamber **101**. The gas inlet port **114** is in fluid communication with the gas compressor **109** via the inlet tube **112**. The heating coil **107** is operably positioned on an inner surface wall **111a** of the vacuum chamber **101**. The heating coil **107** heats the recirculating gas **113** in the inner enclosed space **102** of the vacuum chamber **101** to a preset temperature, for example, a temperature preset between about 30° C. and about 75° C. The recirculating gas **113** heated by the heating coil **107**, contacts the instruments **108** positioned in the inner enclosed space **102** of the vacuum chamber **101** and transfers heat energy into the interstitial cavities **117** and to the surfaces **118** of the accommodated instruments **108** as exemplarily illustrated in FIG. 3B, which shows an enlarged view of a portion marked A in FIG. 3A. As exemplarily illustrated in FIG. 3B, the interstitial cavities **117** comprise, for example, needle grooves, narrow and deep fluid transfer lines, etc., in the instruments **108**. The surfaces **118** of the instruments **108**, for example, cover the total surface area of the instruments **108** including surfaces defined by the interstitial cavities **117**.

[0040] As exemplarily illustrated in FIG. 3A, the vacuum pump **105** is operably connected to a second opening **106**

defined at the second opposing end **101b** of the vacuum chamber **101**. The vacuum pump **105** is in fluid communication with the vacuum chamber **101** via the second opening **106**. The vacuum pump **105** creates a negative gas pressure, for example, a negative pressure preset to between about 2 inches of mercury and about 29 inches mercury, in the inner enclosed space **102** of the vacuum chamber **101** to vaporize the moisture **115** off the accommodated instruments **108** and exhausts the vaporized moisture entrained in the recirculating gas **116**, which may optionally be heated by the heating coil **107** positioned in the inner enclosed space **102** of the vacuum chamber **101**. The vacuum pump **105** is in fluid communication with the condenser **110** via the vacuum pump outlet pipe **119**. In an embodiment, the condenser **110**, operably connected to and in fluid communication with the vacuum pump **105**, receives the vaporized moisture entrained in the heated recirculating gas **116** from the vacuum pump **105** via the vacuum pump outlet pipe **119**. The condenser **110** condenses and reduces moisture from the vaporized moisture entrained in the heated recirculating gas **116** exhausted from the vacuum chamber **101** by the vacuum pump **105**, and feeds a moisture reduced, low humidity recirculating gas into the gas compressor **109** via the condenser outlet pipe **120**.

[0041] The moisture reduced, low humidity recirculating gas from the condenser **110** is fed to the gas compressor **109** and compressed to a preset pressure, for example, a pressure preset to between about 16 psig and 25 psig by the gas compressor **109** and is recirculated back to the vacuum chamber **101**. In an embodiment, the recirculated gas **113** fed to the vacuum chamber **101** is heated by the heating coil **107** to a preset temperature, for example, a temperature of between about 30° C. to about 75° C. in the vacuum chamber **101**.

[0042] FIGS. 4A-4B exemplarily illustrate top perspective views of embodiments of the vacuum assisted dehydration system **100**, showing embodiments of the sealing member **103**. FIG. 4A shows a threadable connection of the sealing member **103** to an opening **104** of the vacuum chamber **101**. The sealing member **103** is configured, for example, as an air tight cap. In an embodiment, the sealing member **103** is a metallic cap **121** concentrically aligned with a rubber washer **122**. The metallic cap **121** is fastened through threads **123** configured at the first opening **104** defined at the first opposing end **101a** of the vacuum chamber **101** as exemplarily illustrated in FIG. 4A. In FIGS. 4A-4B, the gas compressor **109** and the condenser **110** of the vacuum assisted dehydration system **100** are positioned over a saddle member **124** extending outwards from the vacuum chamber **101**.

[0043] FIG. 4B shows a push fit connection of the sealing member **103** to an opening **104** of the vacuum chamber **101**. As exemplarily illustrated in FIG. 4B, in an embodiment, the sealing member **103** is, for example, a push fit seal comprising the metallic cap **121** and the rubber washer **122**. The sealing member **103** push fits to the first opening **104** defined at the first opposing end **101a** of the vacuum chamber **101** to facilitate an air tight seal of the vacuum chamber **101**. The sealing member **103** push fits onto a locking groove **125** positioned proximal to the first opening **104** of the vacuum chamber **101**. In an embodiment, the sealing member **103** is turned, for example, in a clockwise direction to lock the sealing member **103** under the locking groove **125**, and turned in a counterclockwise direction to unlock the sealing member **103** from under the locking groove **125**. In another embodiment, the sealing member **103** is made of a metallic material having a low coefficient of thermal expansion to avoid expan-

sion of the sealing member **103** due to heat produced by the heating coil **107** exemplarily illustrated in FIG. 3A. The metallic material of the sealing member **103** is, for example, aluminum, stainless steel, etc.

[0044] FIG. 5 exemplarily illustrates a rear perspective view of the heating coil **107** of an embodiment of the vacuum assisted dehydration system **100** exemplarily illustrated in FIG. 1 and FIG. 3A, showing safety switches **126** operably connected to the heating coil **107**. In an embodiment, the heating coil **107** is, for example, an electric heating coil configured to heat the recirculating gas in the vacuum chamber **101** exemplarily illustrated in FIG. 1 and FIG. 3A, to a preset temperature, for example, to a temperature between about 30° C. to about 75° C. to facilitate the evaporation of moisture present in the interstitial cavities **117** and on the surfaces **118** of the accommodated instruments **108** exemplarily illustrated in FIGS. 3A-3B. Since excess temperature may damage an instrument **108**, in an embodiment, the vacuum assisted dehydration system **100** further comprises safety switches **126** operably connected to the heating coil **107** to regulate the temperature to a predetermined level in the inner enclosed space **102** of the vacuum chamber **101** exemplarily illustrated in FIG. 3A. A user can manually adjust the temperature settings within the vacuum chamber **101**, or the temperature can be adjusted automatically by setting a temperature within a predetermined range of temperatures according to the type and material of the instrument **108** to be dehydrated. The temperatures can be set using a temperature gauge **127** operably connected to the heating coil **107**.

[0045] FIG. 6 exemplarily illustrates a top perspective view of the vacuum pump **105** of an embodiment of the vacuum assisted dehydration system **100** exemplarily illustrated in FIG. 1 and FIG. 3A, showing a pressure control valve **128** connected to the vacuum pump **105**. In an embodiment, the vacuum pump **105** is, for example, a multistage centrifugal vacuum pump or a multistage reciprocating vacuum pump with a power rating of, for example, about 1 horsepower to about 5 horsepower. In an embodiment, the vacuum assisted dehydration system **100** further comprises a pressure control valve **128** operably connected to the vacuum pump **105** for controlling an amount of the negative gas pressure created within the inner enclosed space **102** of the vacuum chamber **101** to protect the accommodated instruments **108** within the vacuum chamber **101** and to control the rate and extent of moisture evaporation of the moisture off the instruments **108** as exemplarily illustrated in FIG. 3A. A pressure gauge **129** is operably connected to the vacuum pump **105**, for example, via a flexible tube **130**, for example, a hose, a pipe, etc., to measure and display the negative pressure created within the inner enclosed space **102** of the vacuum chamber **101**. A user can set the negative pressure in the vacuum chamber **101** by adjusting the pressure control valve **128**. In an embodiment, the vacuum pump **105** draws down the vacuum in the vacuum chamber **101** to a preset negative pressure, for example, a negative pressure of between about 2 inches of mercury and 29 inches of mercury. In an embodiment, the vacuum pump **105** is operably connected to the second opening **106** of the vacuum chamber **101** through a flexible tube **130**, for example, a hose, a pipe, etc., as exemplarily illustrated in FIG. 3A.

[0046] FIG. 7 exemplarily illustrates a cutaway view of an embodiment of the vacuum assisted dehydration system **100**, showing a suction line **131** connected to an opening **106** of the vacuum chamber **101**. In an embodiment, the vacuum

assisted dehydration system **100** disclosed herein further comprises the suction line **131**, for example, a dental suction line or a medical plumbing line from a dental or medical vacuum system known in the art, operably connected to the second opening **106** of the vacuum chamber **101**. The suction line **131** is a line drawn from one or more dental or medical vacuum systems that can create a negative gas pressure within the vacuum chamber **101** similar to the vacuum pump **105** exemplarily illustrated in FIG. 3A and FIG. 6. An example of a dental vacuum system is a dental suction pump. The suction line **131** produces a preset vacuum pressure, for example, preset to a negative pressure of between about 2 inches of mercury and 29 inches of mercury within the inner enclosed space **102** of the vacuum chamber **101**. Similar to the vacuum pump **105** exemplarily illustrated in FIG. 3A and FIG. 6, the suction line **131** is also in fluid communication with the condenser **110** via a suction outlet pipe **132** to transfer the vaporized moisture entrained in the recirculating gas from the inner enclosed space **102** of the vacuum chamber **101** to the condenser **110**, to allow the dehydration of the instruments **108** positioned in the inner enclosed space **102** of the vacuum chamber **101** as exemplarily illustrated in FIG. 3A. The vaporized moisture entrained in the recirculating gas is exhausted from the suction line **131** to the condenser **110** via the suction outlet pipe **132**.

[0047] FIG. 8 exemplarily illustrates a top perspective view of an embodiment of the vacuum assisted dehydration system **100**, showing components the surface of which are moist, hereinafter referred to as “moist hands”, introduced into an inner enclosed space **102** of the vacuum chamber **101** via an opening **104**. In this embodiment, the vacuum assisted dehydration system **100** does not comprise the sealing member **103** exemplarily illustrated in FIGS. 1-4B and FIG. 7. The sealing member **103** is removed to enable a user to introduce moist hands **133** into the inner enclosed space **102** of the vacuum chamber **101** through the first opening **104**. The vacuum assisted dehydration system **100** disclosed herein dehydrates a user's moist hands **133**, moist surgical gloves, etc., in a dental environment or a medical environment. The vacuum assisted dehydration system **100** comprises the generally cylindrical vacuum chamber **101**, the condenser **110**, the gas compressor **109**, the gas inlet port **114**, the heating coil **107**, and the vacuum pump **105** as disclosed in the detailed description of FIGS. 1-2 and FIG. 3A. The first opening **104** is defined at the first opposing end **101a** of the vacuum chamber **101** and is configured to receive the moist hands **133** into the inner enclosed space **102** of the vacuum chamber **101**.

[0048] In an example, a user introduces his/her hands **133** the surface of which is moist, into the inner enclosed space **102** of the vacuum chamber **101** through the first opening **104**. The recirculating gas heated by the heating coil **107** to a preset temperature of between 30° C. and 75° C. contacts the moist hands **133**, transfers heat energy onto the surface of the moist hands **133** to vaporize moisture present on the moist hands **133**, and removes moisture present on the moist hands **133**. The vacuum pump **105** positioned and operably connected to the second opening **106** of the vacuum chamber **101** creates a negative gas pressure in the inner enclosed space **102** to dehydrate the moist hands **133** and exhausts the vaporized moisture entrained in the heated recirculating gas from the inner enclosed space **102** of the vacuum chamber **101** to the condenser **110**.

[0049] In this embodiment, the vacuum assisted dehydration system **100** provides a transient dehydration region in the

inner enclosed space **102** of the vacuum chamber **101** for dehydrating the moist hands **133** by supplying the recirculating gas from the gas compressor **109** into the inner enclosed space **102** of the vacuum chamber **101**, heating the recirculating gas using the heating coil **107**, allowing the heated recirculating gas to contact the moist hands **133**, and exhausting the vaporized moisture entrained in the heated recirculating gas from the moist hands **133** using the vacuum pump **105** to the condenser **110**. In this embodiment, the recirculated air is used to dry moist hands **133** in the open vacuum chamber **101**. The vacuum assisted dehydration system **100** produces a transient dehydration state in the vacuum chamber **101**, in which moderately heated and moderately pressurized recirculating gas, for example, gas heated to a temperature of about 50° C. and pressurized to between about 16 psig and 25 psig is blown into the inner enclosed space **102** of the vacuum chamber **101**. The vaporized moisture entrained in the heated recirculating gas is exhausted by the vacuum pump **105** into the condenser **110**. Moist hands **133** which are hard to fit into gloves due to moisture induced friction can be dehydrated rapidly in the open vacuum chamber **101** of the vacuum assisted dehydration system **100**.

[0050] FIG. 9A exemplarily illustrates a cutaway view of an embodiment of the vacuum assisted dehydration system **100**, showing a rotary disk assembly **134** positioned in the vacuum chamber **101**. In an embodiment, the vacuum assisted dehydration system **100** disclosed herein further comprises the rotary disk assembly **134** positioned on the inner surface wall **111a** of the vacuum chamber **101**. The rotary disk assembly **134** comprises a disk member **135** and an electric motor **136**. The disk member **135** is axially aligned and fixedly connected to the electric motor **136**, for example, via a locking nut **137**. The disk member **135** fixedly accommodates the instruments **108**. The electric motor **136** is, for example, a vertically oriented electric motor. The sealing member **103** is opened and the instruments **108** are introduced into the inner enclosed space **102** of the vacuum chamber **101**. The instruments **108** are removably attached on gripping members **138** fixedly attached on an upper surface **135a** of the disk member **135**, and the instruments **108** are positioned so that when the disk member **135** is rotated at high revolutions per minute (rpm), the moisture within the interstitial cavities **117** of the instruments **108** is forced towards the open ends or open surfaces of the instruments **108**. The sealing member **103** is then closed and the electric motor **136** is actuated to rotate the disk member **135** at a speed of, for example, about 400 rpm to about 4000 rpm. The centrifugal force generated on the instruments **108** forces the moisture present in the interstitial cavities **117** and on the surfaces **118** of the instruments **108** towards the open, or upper surfaces **118** of the instruments **108**, or the open ends **117a** of the interstitial cavities **117** of the instruments **108** as exemplarily illustrated in FIG. 9B. FIG. 9B exemplarily illustrates an enlarged view of a portion marked B in FIG. 9A of the embodiment of the vacuum assisted dehydration system **100**, showing interstitial cavities **117** and surfaces **118** of an instrument **108**. The moisture in the interstitial cavities **117** of the instruments **108** displaced to the open or outer ends **117a** of the interstitial cavities **117** is further removed by the moisture reduced, low humidity recirculating gas supplied by the gas compressor **109** into the inner enclosed space **102** of the vacuum chamber **101**, by the recirculating gas that is heated by the heating coil **107**, and by the negative gas pressure

created in the vacuum chamber **101** by the vacuum pump **105** as disclosed in the detailed description of FIGS. 3A-3B.

[0051] FIG. 10 exemplarily illustrates a block diagram showing a process for dehydrating instruments **108** within the vacuum assisted dehydration system **100**. The moisture removal process is a recirculating loop shown schematically in FIG. 10. As exemplarily illustrated in FIG. 3A, the instruments **108** from which moisture is to be removed are positioned within the inner enclosed space **102** of the vacuum chamber **101** of the vacuum assisted dehydration system **100**. The gas compressor **109** supplies a recirculating gas pressurized to a preset pressure, for example, preset to a pressure between about 16 psig and 45 psig, into the inner enclosed space **102** of the vacuum chamber **101**. The recirculating gas is heated by the heating coil **107** to a preset temperature, for example, a temperature preset between about 30° C. to 75° C. The heated recirculating gas contacts the instruments **108** positioned in the inner enclosed space **102** of the vacuum chamber **101**; the heated recirculating gas and the vacuum within the vacuum chamber **101** vaporize the moisture from the interstitial cavities **117** and surfaces **118** of the instruments **108** exemplarily illustrated in FIG. 3B.

[0052] The vacuum pump **105** creates a preset negative pressure, for example, a negative pressure set between about 2 inches of mercury and 29 inches of mercury in the inner enclosed space **102** of the vacuum chamber **101**, which vaporizes the moisture off the instruments **108** and exhausts the vaporized moisture entrained in the heated recirculating gas to the condenser **110** via the vacuum pump outlet pipe **119** exemplarily illustrated in FIG. 3A. The inner enclosed space **102** within the vacuum chamber **101** is maintained at a negative pressure, preset at a negative pressure of between about 2 inches mercury and about 29 inches mercury to allow the moisture in the interstitial cavities **117** and surfaces **118** of the instruments **108** to volatilize off the instruments **108** and be entrained in the recirculating gas in the vacuum chamber **101**. The recirculating gas from the vacuum chamber **101** is exhausted by the vacuum pump **105** to the condenser **110** where the moisture is condensed out by dropping the temperature of the vaporized moisture entrained in the recirculating gas in the condenser **110**. The condenser **110** condenses the vaporized moisture in the recirculating gas to water **1001** by contacting the recirculating gas with a cooling coil **110a** in which a refrigerant is recirculated at a preset temperature, for example, a temperature preset between about 10° C. to about -2° C. The moisture reduced, low humidity recirculating gas is fed from the condenser **110** to the gas compressor **109** via the condenser outlet pipe **120** exemplarily illustrated in FIG. 3A. The moisture reduced, low humidity recirculating gas is pumped by the gas compressor **109** at a preset pressure, for example, a pressure between about 15 psig and 40 psig back into the inner closed space **102** of the vacuum chamber **101**.

[0053] FIGS. 11A-11B exemplarily illustrate a method for dehydrating one or more instruments **108**. The vacuum assisted dehydration system **100** comprising the generally cylindrical vacuum chamber **101**, the heating coil **107**, the sealing member **103**, the vacuum pump **105**, the condenser **110**, the gas compressor **109**, and the gas inlet port **114** as exemplarily illustrated in FIGS. 3A-3B and as disclosed in the detailed description of FIGS. 3A-3B is provided **1101**. The sealing member **103** is opened to allow a user to introduce **1102** one or more instruments **108** into the inner enclosed space **102** of the vacuum chamber **101**. The gas compressor **109** recirculates **1103** a gas pressurized to a preset

pressure, for example, a pressure between about 15 psig and 40 psig into the inner enclosed space **102** of the vacuum chamber **101** via the inlet tube **112**. The recirculating gas is fed **1104** from the gas compressor **109** into the inner enclosed space **102** of the vacuum chamber **101** via the gas inlet port **114**.

[0054] The heating coil **107** heats **1105** the fed recirculating gas in the inner enclosed space **102** of the vacuum chamber **101** to a preset temperature, for example, to a temperature between about 30° C. and about 75° C. The heated recirculating gas contacts the instruments **108** positioned within the inner enclosed space **102** of the vacuum chamber **101** and transfers **1106** heat energy into interstitial cavities **117** and to the surfaces **118** of the instruments **108** to vaporize moisture present in the interstitial cavities **117** and on the surfaces **118** of the instruments **108** under a vacuum created in the inner enclosed space **102** by the vacuum pump **105**. The vacuum pump **105** creates **1107** a negative gas pressure in the inner enclosed space **102** of the vacuum chamber **101** and exhausts **1108** the vaporized moisture entrained in the heated recirculating gas from the inner enclosed space **102** of the vacuum chamber **101** to the condenser **110** via the vacuum pump **105** and the vacuum pump outlet pipe **119**. The condenser **110** condenses **1109** and reduces moisture from the vaporized moisture entrained in the heated recirculating gas to produce a moisture reduced, low humidity recirculating gas. The moisture reduced, low humidity recirculating gas is fed **1110** from the condenser **110** through the condenser outlet pipe **120** into the gas compressor **109**. The moisture reduced, low humidity recirculating gas is recirculated **1011** from the gas compressor **109** back to the vacuum chamber **101** via the gas inlet port **114**. The embodiment of the vacuum assisted dehydration system **100** exemplarily illustrated in FIG. 8, is used for dehydrating moist components, for example, moist hands **133**, moist gloves, etc.

[0055] The foregoing examples have been provided merely for the purpose of explanation and are in no way to be construed as limiting of the present invention disclosed herein. While the invention has been described with reference to various embodiments, it is understood that the words, which have been used herein, are words of description and illustration, rather than words of limitation. Further, although the invention has been described herein with reference to particular means, materials, and embodiments, the invention is not intended to be limited to the particulars disclosed herein; rather, the invention extends to all functionally equivalent structures, methods and uses, such as are within the scope of the appended claims. Those skilled in the art, having the benefit of the teachings of this specification, may affect numerous modifications thereto and changes may be made without departing from the scope and spirit of the invention in its aspects.

We claim:

1. A vacuum assisted dehydration system for dehydrating one or more instruments, said vacuum assisted dehydration system comprising:

- a generally cylindrical vacuum chamber defining an inner enclosed space configured to accommodate said one or more instruments;
- a sealing member removably attached to a first opening defined at a first opposing end of said generally cylindrical vacuum chamber, said sealing member configured to open said generally cylindrical vacuum chamber to

allow said one or more instruments to be introduced into said inner enclosed space of said generally cylindrical vacuum chamber; and

- a vacuum pump operably connected to a second opening defined at a second opposing end of said generally cylindrical vacuum chamber, wherein said vacuum pump is in fluid communication with said generally cylindrical vacuum chamber via said second opening, and wherein said vacuum pump is configured to create a negative gas pressure in said inner enclosed space of said generally cylindrical vacuum chamber to dehydrate said accommodated one or more instruments after said generally cylindrical vacuum chamber is closed by said sealing member.

2. The vacuum assisted dehydration system of claim 1, further comprising a heating coil operably positioned on an inner surface wall of said generally cylindrical vacuum chamber, wherein said heating coil is configured to heat a recirculating gas in said inner enclosed space of said generally cylindrical vacuum chamber to facilitate removal of moisture from said accommodated one or more instruments and accelerate said dehydration of said accommodated one or more instruments.

3. A vacuum assisted dehydration system for dehydrating one or more instruments, said vacuum assisted dehydration system comprising:

- a generally cylindrical vacuum chamber comprising a surface wall, said surface wall defining an inner enclosed space configured to accommodate said one or more instruments, said surface wall of said generally cylindrical vacuum chamber configured to reflect heat;
- a sealing member removably attached to a first opening defined at a first opposing end of said generally cylindrical vacuum chamber, said sealing member configured to open said generally cylindrical vacuum chamber to allow said one or more instruments to be introduced into said inner enclosed space of said generally cylindrical vacuum chamber;
- a gas compressor positioned proximal to and in fluid communication with said generally cylindrical vacuum chamber via an inlet tube, said gas compressor configured for recirculating a gas pressurized to a preset pressure into said inner enclosed space of said generally cylindrical vacuum chamber via said inlet tube;
- a gas inlet port defined on said surface wall of said generally cylindrical vacuum chamber and in fluid communication with said gas compressor via said inlet tube, said gas inlet port configured to feed said recirculating gas from said gas compressor into said inner enclosed space of said generally cylindrical vacuum chamber via said inlet tube;
- a heating coil operably positioned on an inner said surface wall of said generally cylindrical vacuum chamber, said heating coil configured to heat said recirculating gas in said inner enclosed space of said generally cylindrical vacuum chamber, wherein said heated recirculating gas contacts said accommodated one or more instruments positioned in said inner enclosed space of said generally cylindrical vacuum chamber and transfers heat energy into interstitial cavities and to surfaces of said accommodated one or more instruments to vaporize moisture present in said interstitial cavities and on said surfaces of said accommodated one or more instruments; and

a vacuum pump operably connected to a second opening defined at a second opposing end of said generally cylindrical vacuum chamber, wherein said vacuum pump is in fluid communication with said generally cylindrical vacuum chamber via said second opening, and wherein said vacuum pump is configured to create a negative gas pressure in said inner enclosed space of said generally cylindrical vacuum chamber to dehydrate said accommodated one or more instruments after said generally cylindrical vacuum chamber is closed by said sealing member, and exhaust said vaporized moisture entrained in said heated recirculating gas from said inner enclosed space of said generally cylindrical vacuum chamber.

4. The vacuum assisted dehydration system of claim 3, further comprising a condenser in upstream communication with said vacuum pump via a vacuum pump outlet pipe, and in downstream communication with said gas compressor via a condenser outlet pipe, wherein said condenser is configured to receive said vaporized moisture entrained in said heated recirculating gas from said vacuum pump, and wherein said condenser is further configured to condense and reduce moisture from said vaporized moisture entrained in said heated recirculating gas exhausted from said generally cylindrical vacuum chamber by said vacuum pump, and feed a moisture reduced, low humidity recirculating gas into said gas compressor.

5. The vacuum assisted dehydration system of claim 3, wherein said gas is an inert gas.

6. The vacuum assisted dehydration system of claim 3, wherein said heating coil is an electric heating coil.

7. The vacuum assisted dehydration system of claim 3, wherein said surface wall of said generally cylindrical vacuum chamber is made of aluminum.

8. The vacuum assisted dehydration system of claim 3, wherein said sealing member is a metallic cap concentrically aligned with a washer, wherein said metallic cap is fastened through threads configured at said first opening defined at said first opposing end of said generally cylindrical vacuum chamber.

9. The vacuum assisted dehydration system of claim 3, wherein said sealing member is a push fit seal comprising a metallic cap and a washer, wherein said sealing member is configured to push fit to said first opening defined at said first opposing end of said generally cylindrical vacuum chamber to facilitate an air tight seal of said generally cylindrical vacuum chamber.

10. The vacuum assisted dehydration system of claim 3, wherein said sealing member is made of a metallic material having a low coefficient of thermal expansion to avoid expansion of said sealing member due to heat produced by said heating coil.

11. The vacuum assisted dehydration system of claim 3, wherein said vacuum pump is one of a multistage centrifugal vacuum pump and a multistage reciprocating vacuum pump.

12. The vacuum assisted dehydration system of claim 3, wherein said vacuum pump is operably connected to said second opening of said generally cylindrical vacuum chamber through a flexible tube.

13. The vacuum assisted dehydration system of claim 3, further comprising one or more pressure control valves operably connected to said vacuum pump, wherein said one or more pressure control valves are configured to control an amount of said negative gas pressure created within said inner enclosed space of said generally cylindrical vacuum chamber

to protect said accommodated one or more instruments within said generally cylindrical vacuum chamber.

14. The vacuum assisted dehydration system of claim 3, further comprising a suction line operably connected to said second opening of said generally cylindrical vacuum chamber, wherein said suction line is configured to produce a preset vacuum pressure within said inner enclosed space of said generally cylindrical vacuum chamber.

15. The vacuum assisted dehydration system of claim 3, further comprising safety switches operably connected to said heating coil to regulate temperature to a predetermined level in said inner enclosed space of said generally cylindrical vacuum chamber.

16. The vacuum assisted dehydration system of claim 3, further comprising a rotary disk assembly positioned on an inner said surface wall of said generally cylindrical vacuum chamber, wherein said rotary disk assembly comprises a disk member and an electric motor, wherein said disk member is axially aligned and fixedly connected to said electric motor and configured to fixedly accommodate said one or more instruments, and wherein said electric motor is configured to rotate said disk member at a sufficient speed to generate a centrifugal force sufficient to force said moisture present in said interstitial cavities and on said surfaces of said accommodated one or more instruments to open ends and open surfaces of said accommodated one or more instruments for removal by said recirculating gas fed by said gas compressor into said inner enclosed space of said generally cylindrical vacuum chamber, by said recirculating gas heated by said heating coil, and by said negative gas pressure created in said generally cylindrical vacuum chamber by said vacuum pump.

17. A vacuum assisted dehydration system for dehydrating one or more components containing moisture on surfaces of said one or more components, said vacuum assisted dehydration system comprising:

- a generally cylindrical vacuum chamber comprising a surface wall, said surface wall defining an inner enclosed space configured to accommodate said one or more components containing said moisture on said surfaces of said one or more components, said surface wall of said generally cylindrical vacuum chamber configured to reflect heat;
- a first opening defined at a first opposing end of said generally cylindrical vacuum chamber, said first opening configured to receive said one or more components into said inner enclosed space of said generally cylindrical vacuum chamber;
- a gas compressor positioned proximal to and in fluid communication with said generally cylindrical vacuum chamber via an inlet tube, said gas compressor configured for recirculating a gas pressurized to a preset pressure into said inner enclosed space of said generally cylindrical vacuum chamber via said inlet tube;
- a gas inlet port defined on said surface wall of said generally cylindrical vacuum chamber and in fluid communication with said gas compressor via said inlet tube, said gas inlet port configured to feed said recirculating gas from said gas compressor into said inner enclosed space of said generally cylindrical vacuum chamber via said inlet tube;
- a heating coil operably positioned on an inner said surface wall of said generally cylindrical vacuum chamber, said heating coil configured to heat said recirculating gas in said inner enclosed space of said generally cylindrical

vacuum chamber, wherein said heated recirculating gas contacts said one or more components positioned in said inner enclosed space of said generally cylindrical vacuum chamber and transfers heat energy onto said one or more components to vaporize said moisture contained thereon; and

- a vacuum pump operably connected to a second opening defined at a second opposing end of said generally cylindrical vacuum chamber, wherein said vacuum pump is in fluid communication with said generally cylindrical vacuum chamber via said second opening, and wherein said vacuum pump is configured to create a negative gas pressure in said inner enclosed space of said generally cylindrical vacuum chamber to dehydrate said one or more components and exhaust said vaporized moisture entrained in said heated recirculating gas from said inner enclosed space of said generally cylindrical vacuum chamber.

18. The vacuum assisted dehydration system of claim 17 configured to provide a transient dehydration region in said inner enclosed space of said generally cylindrical vacuum chamber for dehydrating said one or more components by recirculating said gas from said gas compressor into said inner enclosed space of said generally cylindrical vacuum chamber, heating said recirculating gas using said heating coil, allowing said heated recirculating gas to contact said one or more components, and exhausting said vaporized moisture entrained in said heated recirculating gas from said one or more components via said vacuum pump.

19. The vacuum assisted dehydration system of claim 17, further comprising a condenser in upstream communication with said vacuum pump via a vacuum pump outlet pipe, and in downstream communication with said gas compressor via a condenser outlet pipe, wherein said condenser is configured to receive said vaporized moisture entrained in said heated recirculating gas from said vacuum pump, and wherein said condenser is further configured to condense and reduce moisture from said vaporized moisture entrained in said heated recirculating gas exhausted from said generally cylindrical vacuum chamber by said vacuum pump, and feed a moisture reduced, low humidity recirculating gas into said gas compressor.

20. A method for dehydrating one or more instruments, said method comprising:

- providing a vacuum assisted dehydration system comprising:
 - a generally cylindrical vacuum chamber comprising a surface wall, said surface wall defining an inner enclosed space configured to accommodate said one or more instruments;
 - a heating coil operably positioned on an inner said surface wall of said generally cylindrical vacuum chamber;
 - a sealing member removably attached to a first opening defined at a first opposing end of said generally cylindrical vacuum chamber;
 - a vacuum pump operably connected to a second opening defined at a second opposing end of said generally cylindrical vacuum chamber, wherein said vacuum pump is in fluid communication with said generally cylindrical vacuum chamber via said second opening;
 - a condenser in upstream communication with said vacuum pump via a vacuum pump outlet pipe, and in

downstream communication with a gas compressor via a condenser outlet pipe;
said gas compressor positioned proximal to and in fluid communication with said generally cylindrical vacuum chamber via an inlet tube; and
a gas inlet port defined on said surface wall of said generally cylindrical vacuum chamber and in fluid communication with said gas compressor via said inlet tube;
opening said sealing member of said vacuum assisted dehydration system and introducing said one or more instruments into said inner enclosed space of said generally cylindrical vacuum chamber of said vacuum assisted dehydration system;
recirculating a gas pressurized to a preset pressure from said gas compressor of said vacuum assisted dehydration system into said inner enclosed space of said generally cylindrical vacuum chamber via said inlet tube;
feeding said recirculating gas into said inner enclosed space of said generally cylindrical vacuum chamber via said gas inlet port;
heating said fed recirculating gas in said inner enclosed space of said generally cylindrical vacuum chamber by said heating coil of said vacuum assisted dehydration system, wherein said heated recirculating gas contacts said introduced one or more instruments accommodated in said inner enclosed space of said generally cylindrical

vacuum chamber and transfers heat energy into interstitial cavities and to surfaces of said accommodated one or more instruments to vaporize moisture present in said interstitial cavities and on said surfaces of said accommodated one or more instruments;
creating a negative gas pressure in said inner enclosed space of said generally cylindrical vacuum chamber by said vacuum pump of said vacuum assisted dehydration system;
exhausting, by said negative gas pressure, said vaporized moisture entrained in said heated recirculating gas from said inner enclosed space of said generally cylindrical vacuum chamber to said condenser via said vacuum pump and said vacuum pump outlet pipe;
condensing and reducing moisture from said vaporized moisture entrained in said heated recirculating gas by said condenser of said vacuum assisted dehydration system to produce a moisture reduced, low humidity recirculating gas;
feeding said moisture reduced, low humidity recirculating gas from said condenser into said gas compressor via said condenser outlet pipe; and
recirculating said moisture reduced, low humidity recirculating gas from said gas compressor back to said generally cylindrical vacuum chamber via said gas inlet port.

* * * * *